



1-855-912-1947 ☎

www.goodearthdrilling.com 🌐

info@goodearthdrilling.com ✉

IR TH75E Reconditioned 2021

SPECIFICATIONS RIG 154

Engine	<ul style="list-style-type: none"> Cummins ISX 550 HP Cummins KT19 Deck
Derrick	<ul style="list-style-type: none"> 31' IR mast rated @ 80,000Lbs 29ft stroke angle capable
Pullback (Hook load)	<ul style="list-style-type: none"> 70,000LBS
Top Drive	<ul style="list-style-type: none"> 8,000 ft-lbs. torque 4 motor top head drive
Top Drive Speed	<ul style="list-style-type: none"> 0-130RPM
Down Push	<ul style="list-style-type: none"> 30,000LBS
Mud Pump	<ul style="list-style-type: none"> 5x6 Gardner Denver FXXH Duplex pump
Main Winch (Single line)	<ul style="list-style-type: none"> 25,000 LBS x 3/4" wire rope
Wire Line	<ul style="list-style-type: none"> 8000 LBS x 1/4" non rotating wire rope
Air compressor	<ul style="list-style-type: none"> IR 1050/350 CFM on board KTA 1150 Deck engine

TOOLING

Drill Pipe	<ul style="list-style-type: none"> CP-HD Core pipe as required
Breakout System	<ul style="list-style-type: none"> Hydraulic Petol chain tongs
Casing Running Equipment	<ul style="list-style-type: none"> HIR 5 1/2", 7", 8 5/8", 9 5/8" Casing elevators Top drive casing circulating and cementing heads
Wireline Coring	<ul style="list-style-type: none"> 4 5/8" CP-HD Core pipe or 6 5/8" CP-HD 3 m 3" core barrel with two 2 7/8" inner bbl. 1.5m barrel with 6" core Christensen overshot core retrieval assembly

SUPPORT EQUIPMENT

Generator	<ul style="list-style-type: none"> 20 KW 490/208v Stamford generators / Light tower Light tower with (4) 1000-watt halogen lights
Boiler	<ul style="list-style-type: none"> 30HP Williams and Davis 120 psi 2002 Sterling LT9500 Truck Mounted 2400 L fuel tank 5000 L water tank
Core Van	<ul style="list-style-type: none"> IHC 4300 series 24' Cube van box 12' Core mark table 12'-Fold down work platform 4' x 8' Dry crew change area
Pipe Truck	<ul style="list-style-type: none"> Kenworth T300 with Cassady hydraulic pipe arm, angle capable